



TECHNICAL DETAILS - O-LITE

- Light Transmission of clear glass = 70%
- Light Transmission of blue glass = 40%
- Light Transmission of bronze glass = 70%
- Light Transmission of opaque/obscure glass = 70%
- UV Blocked = 90%
- Spacer bar system = warm edge, non-metallic Tri-seal/Super spacer dessicant impregnated
- Toughened to BS EN 12150
- Manufactured to BS EN 1279 Part 2 & 3
- Structural Frame = A satin black durable polyseter powder coated aluminium integrated upstand, with a minimum thickness of aluminium available for heat transfer. Thermally broken by polyethylene foam for enhanced thermal performance

ROOF Maker
 1 Pinfold Road, Thurmaston
 Leicester LE4 8AS
 Tel: 0116 269 6297
 Fax: 0116 269 6291
 Email: sales@roof-maker.co.uk



Title: **O-LITE PRODUCT SPECIFICATION**

THIS DRAWING IS FOR REFERENCE ONLY. PLEASE REPORT ANY DISCREPANCIES TO THE DESIGNER BEFORE ANY WORKS COMMENCE. ALL DIMENSIONS TO BE CHECKED ON SITE BEFORE ANY WORKS COMMENCE.	Reference: O-Lite	Scale: 1:1 @ A4
	Date: 21/02/2017	Revision NO: A
	Drawn: TH Checked: SM	