Minimum fall 15 ° (inc roof)
Maximum fall 75 ° (inc roof)

IF INCLUDING BLACKOUT BLINDS

When blinds are selected, plaster up to blind trim

Black out blind option

Plasterboard to be finished as illustrated. Run into dedicated white internal trim, this will also act as your stop bead to ensure a neat finish when plastering

Do not lift by glass

Screw fix timber kerb to fix luxlite to roof using brackets and screws provided - refer to step by step installation guide

20

Lift from here (apron lip)

Plywood Deck

Roof Tiles

White powder coated internal trim (factory applied)

Max 15mm Plasterboard

Internal sizes
taken from here
(size ordered = size of timber structural opening)

Tile Battens to be ran upto the side of the flashing tray

Roofing underfelt to be fitted onto roof, flush to the edge of the structural opening prior to fitting rooflight

ROOF MAKER
WORLD CLASS ROOFLIGHTS

Roof Maker Ltd
1 Pinfold Road , Thurmaston
Leicester, LE4 8AS
Tel: 0116 269 6297
Fax: 0116 269 6291
Email: sales@roof-maker.co.uk

Title: LUXLITE TRIPLE GLAZED (FIXED) - TYPICAL FITTING GUIDELINES - WARM DECK ROOF

THIS DRAWING IS FOR REFERENCE ONLY. PLEASE REPORT ANY DISCREPANCIES TO THE DESIGNER BEFORE ANY WORKS COMMENCE. ALL DIMENSIONS ARE IN mm. ALL DIMENSIONS TO BE CHECKED ON SITE BEFORE ANY WORKS COMMENCE.

Date: 10/07/2019

Drawn: CS Checked: SM

Scale: Approx. 1:10 @A4